

LEDinspect PIVOT 700

Inspection lights



Multi-Angle Flex & Twist

High flexibility and diverse adjustment possibilities thanks to multi angle positioning



700 Lumen

3 light functions: - Up to 700lm - high;- Up to 280lm - low



Magnets on base and back

Easily direct light where it's needed most



2-year OSRAM Guarantee*

Systematic quality assurance measures underpin the premium workmanship and functionality of our products. Innovative technology and excellent quality really pay dividends for our customers



Light is versatile

With the PIVOT 700, you can easily control the direction of the light beam.

A light output of up to 700 lumens and a colour temperature of up to 6000K, make the PIVOT 700 ideal for use in workshops and beyond. Lightweight, robust and with 360° rotation and 180° flex function, it is a suitable tool for targeted lighting. Mains charger included. In addition, OSRAM provides a 2-year guarantee on this product*

Technical data

Product information

Application (Category and Product specific)	LED inspection lights
---	-----------------------

General Product Information

Global order reference	LEDIL420
------------------------	----------


Electrical Data

Nominal wattage	6 W
-----------------	-----

Photometric Data

Color temperature	6500 K
Nominal luminous flux	700 lm
Light color LED	White

Physical Attributes & Dimensions



Product weight	320.00 g
Length	245.0 mm
Width	45.0 mm
Height	45.0 mm

LED module information

Number of LEDs per module	1
---------------------------	---

Colors & materials

Base color	Black / Orange
------------	----------------

Lifetime Data

Product datasheet

Guarantee	2 years
Nominal lifetime	17520 hr

Additional product data

Type of Battery	Rechargeable
Number of included batteries	1
Scope of battery	Yes

Capabilities

Technology	LED
------------	-----

Certificates & standards

Standards	CE, EMC, MSDS, ROHS, UKCA
IK Class	IK07

Logistical data

Watt hour per battery	7.40
-----------------------	------

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Declaration no. in SCIP database	In work

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172434713	INSPECTION LAMP	Folding carton box 1	70 mm x 55 mm x 255 mm	0.98 dm ³	500.00 g
4062172434720	INSPECTION LAMP	Shipping carton box 6	305 mm x 190 mm x 160 mm	9.27 dm ³	3000.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

File	
	User instruction LEDinspect LEDIL420

Product datasheet



User instruction
GPRS_Safety symbols instructions

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

OSRAM