

# JOCKEY WHEEL ASSEMBLIES

## 34MM, 43MM & 48MM

### RCT239 34mm Jockey Wheel Assembly including clamp

#### Features

- **Fully retractable, wind down jockey wheel**  
Easy manoeuvring of trailer
- **34mm diameter shaft**  
Used on smaller trailers like camping, motorbike, boat and dinghy trailers
- **100Kg static load**  
Suitable for smaller trailers
- **Fitted with 34mm jockey wheel clamp**  
Easily fits to trailer chassis
- **Made from zinc plated steel**  
Corrosion resistant



### RCT240 43mm Jockey Wheel Assembly including clamp

#### Features

- **Fully retractable, wind down jockey wheel**  
Easy manoeuvring of trailer
- **43mm diameter shaft**  
Used on older horse boxes, plant, flatbed trailers
- **150Kg static load**  
Suitable for medium sized flatbed trailers
- **Fitted with 43mm jockey wheel clamp**  
Easily fits to trailer chassis
- **Made from zinc plated steel**  
Corrosion resistant



### RCT245 48mm Jockey Wheel Assembly including clamp

#### Features

- **Fully retractable, wind down jockey wheel**  
Easy manoeuvring of trailer
- **48mm diameter shaft**  
Most popular size and usually fit to many newer trailers and caravans
- **150Kg static load**  
Suitable for larger sized flatbed trailers and caravans
- **Fitted with 48mm jockey wheel clamp**  
Easily fits to trailer chassis using the clamp or directly through the coupling body
- **Made from zinc plated steel**  
Corrosion resistant



### RCT246 48mm Jockey Wheel Assembly with pneumatic tyre including clamp

#### Features


- **Fully retractable, wind down jockey wheel**  
Easy manoeuvring of trailer
- **48mm diameter shaft**  
Most popular size and usually fit to many newer trailers and caravans
- **Large 260 x 85mm pneumatic tyre**  
Suitable for larger sized trailers and caravans when on softer ground. Great for off road use
- **150Kg static load**  
Suitable for larger sized flatbed trailers and caravans
- **Fitted with 48mm jockey wheel clamp**  
Easily fits to trailer chassis using the clamp or directly through the coupling body
- **Made from zinc plated steel**  
Corrosion resistant



#### Specifications

Product Code	RCT239	RCT240	RCT245	RCT246
Outer tube diameter	34mm	43mm	48mm	48mm
Maximum static load capacity	100Kg	150Kg	150Kg	150Kg
Tyre size	160 x 42mm	200 x 50mm	200 x 50mm	260 x 85mm
Height extension range	220mm	220mm	220mm	220mm
Weight	2.6Kg	3.60Kg	4.71Kg	4.59Kg
Dimensions	840 x 160 x 40mm	849 x 256 x 136mm	840 x 260 x 80mm	840 x 260 x 80mm
Case Quantity	2	2	2	2
Barcode	5055175253404	5011274902407	5055175213743	5055175253411

#### Ring Automotive Limited

Gelderd Road, Leeds, LS12 6NA United Kingdom  
 Telephone: +44 (0)113 213 2000 . Fax: +44 (0)113 231 0266  
 Email: [ordering@ringautomotive.com](mailto:ordering@ringautomotive.com) . [www.ringautomotive.com](http://www.ringautomotive.com)  
 /ringautomotive

#### Authorised Representative:

**OSRAM GmbH**  
 Nonnendammallee 44, 13629 Berlin, Germany  
 Email: [automotive-service@osram.com](mailto:automotive-service@osram.com)  
[www.osram.com](http://www.osram.com)