PROFESSIONAL LITHIUM JUMP STARTER



































- 3000/1800 Peak Amps & 1500/900 Starting Amps
- BOOST to start batteries as low as 0V
- Auto battery voltage selection between 12V and 24V systems
- 75% lighter Than an equivalent Lead Acid Jumpstarter
- Multiple safety protections
- Powerbank USB-A 5V/2.4A DC 12V/8A
- Worklight LED light 2 levels SOS Blink 2 levels

Specifications

Product Code	RPPL3000
Voltage	12/24V DC
Internal Battery Voltage (nominal)	54,000mAh (198.8Wh)
Starting Current	12/24V 1500/900A
Peak Current	12/24V 3000/1800A
Max Cranking Time	2 secs
Battery Type	Lithium-ion Cobolt LiCo02
Battery Capacity	54,000mAh (198.8Wh)
Operating Temperature	-22°C to +55°C
Charging input	13.8V DC 2A 27.6W
Weight	5.6Kg
Product Dimensions	L298 x H298 x W143mm
Pack Dimensions	L330 x H340 x W175mm
Case Quantity	2 x 1
Barcode	5055175251936



Ring Automotive Limited

Gelderd Road, Leeds, LS12 6NA United Kingdom Telephone +44 (0)113 213 2000 . Fax +44 (0)113 231 0266 Email: autosales@ringautomotive.com . www.ringautomotive.com

If O in I /ringautomotive

Authorised Representative: OSRAM GmbH

Nonnendammallee 44, 13629 Berlin, Germany Email: automotive-service@osram.com

www.osram.com